



Safety Data Sheet

Copyright, 2018 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-8072-6	Version Number:	8.00
Issue Date:	05/22/18	Supersedes Date:	12/27/17

SECTION 1: Identification

1.1. Product identifier

D140, Wheel Brightener (26-86A): D14001, D14005, D14025, D14055

Product Identification Numbers

14-1000-0213-9, 14-1000-0214-7, 14-1000-0217-0, 14-1000-0219-6

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Wheel cleaner

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	17991 Mitchell South, Irvine, CA 92614, USA
Telephone:	949-752-8000 (Fax: 949-752-5784)

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Corrosive to metal: Category 1.

Acute Toxicity (oral): Category 4.

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

May be corrosive to metals.

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes damage to organs:

cardiovascular system |

respiratory system |

Causes damage to organs through prolonged or repeated exposure:

musculoskeletal system |

kidney/urinary tract |

respiratory system |

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Call a POISON CENTER or doctor/physician if you feel unwell.

Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns. May cause chemical respiratory tract burns.

10% of the mixture consists of ingredients of unknown acute dermal toxicity.

4% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	70 - 90 Trade Secret *
Ammonium Bifluoride	1341-49-7	5 - 10 Trade Secret *
Sodium Xylene Sulfonate	1300-72-7	1 - 5 Trade Secret *
Ethoxylated Alcohols	68439-46-3	0.5 - 1.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. Get immediate medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
 Carbon dioxide
 Hydrogen Fluoride
 Irritant Vapors or Gases

Condition

During Combustion
 During Combustion
 During Combustion
 During Combustion

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Absorb spillage to prevent material damage. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Collect the resulting residue containing solution. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not breathe thermal decomposition products. Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from heat. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Odor, Color, Grade:	Water-thin purple liquid with sweet odor.
Odor threshold	<i>No Data Available</i>
pH	4.5 - 5.5
Melting point	<i>Not Applicable</i>
Boiling Point	210 °F
Flash Point	Flash point > 93 °C (200 °F) [<i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>

Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Density	1.04 g/cm ³
Specific Gravity	1.04 - 1.07 [Ref Std:WATER=1]
Solubility in Water	Complete
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	1 % weight
Percent volatile	<i>No Data Available</i>
VOC Less H ₂ O & Exempt Solvents	5.45 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

Reacts with metals/glass to form Hydrofluoric acid

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur. Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Corrosion: Signs/symptoms may include nasal discharge, severe nose and throat pain, chest tightness and pain, coughing up blood, wheezing, and breathlessness, possibly progressing to respiratory failure.

May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Prolonged or repeated exposure may cause target organ effects:

Hard Tissue Effects: Signs/symptoms may include color changes in the teeth and nails; changes in development of bone, teeth or nails; weakening of the bones; and/or hair loss.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Ammonium Bifluoride	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.74 mg/l
Ammonium Bifluoride	Ingestion	Rat	LD50 60 mg/kg
Sodium Xylene Sulfonate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sodium Xylene Sulfonate	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethoxylated Alcohols	Dermal	Rabbit	LD50 > 2,000 mg/kg
Ethoxylated Alcohols	Ingestion	Rat	LD50 1,378 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Ethoxylated Alcohols	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Ethoxylated Alcohols	Professional judgement	Corrosive

Skin Sensitization

Name	Species	Value
Ethoxylated Alcohols	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Ethoxylated Alcohols	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Ethoxylated Alcohols	Dermal	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
Ethoxylated Alcohols	Dermal	Not classified for development	Rat	NOAEL 250 mg/kg/day	2 generation
Ethoxylated Alcohols	Dermal	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethoxylated Alcohols	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethoxylated Alcohols	Dermal	kidney and/or bladder hematopoietic system	Not classified	Rat	NOAEL 125 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

DOTG:

1 Gallon: LIMITED QUANTITY

5, 55, 250 Gallon: UN2817, AMMONIUM HYDROGENDIFLOURIDE, SOLLUTION, 8, (6.1), III

DOTW:

1 Gallon: UN2817, AMMONIUM HYDROGENDIFLOURIDE, SOLLUTION, 8, (6.1), III, LIMITED QUANTITY

5, 55, 250 Gallon: UN2817, AMMONIUM HYDROGENDIFLOURIDE, SOLLUTION, 8, (6.1), III

IATA:

MEGUIAR'S PACKAGING DOES NOT MEET REGULAORY AGENCY REQUIREMENTS.

IMO:

1 Gallon: UN2817, AMMONIUM HYDROGENDIFLOURIDE, SOLLUTION, 8, (6.1), III, LIMITED QUANTITY
5, 55, 250 Gallon: UN2817, AMMONIUM HYDROGENDIFLOURIDE, SOLLUTION, 8, (6.1), III

Please contact the emergency numbers listed on the first page of the SDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Corrosive to metal

Health Hazards

Acute toxicity

Hazard Not Otherwise Classified (HNOC)

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Ammonium Bifluoride (AMMONIA COMPOUNDS)	1341-49-7	5 - 10

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 26-8072-6 **Version Number:** 8.00
Issue Date: 05/22/18 **Supersedes Date:** 12/27/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that

the user evaluate theMeguiar's, Inc.product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc.provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,Meguiar's, Inc.makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly fromMeguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com