



Safety Data Sheet

Copyright, 2016 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|---------------|
| Document Group: | 36-5949-7 | Version Number: | 1.00 |
| Issue Date: | 08/30/16 | Supersedes Date: | Initial Issue |

Product identifier

G8800, Perfect Clarity Glass Care Kit: G84 and G85

Supplier's details

MANUFACTURER: Meguiar's, Inc.
DIVISION: Meguiar's

ADDRESS: 17991 Mitchell South, Irvine, CA 92614, USA
Telephone: 949-752-8000 (Fax: 949-752-5784)

Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

G84 and G85

TRANSPORTATION INFORMATION

DOTG:
LIMITED QUANTITY

DOTW:
UN 1987, ALCOHOL, N.O.S., (ISOPROPYL ALCOHOL AND 1-PROPOXY-2-PROPANOL), 3, II, LIMITED QUANTITY

IATA:
UN1987, ALCOHOL, N.O.S., (ISOPROPYL ALCOHOL AND 1-PROPOXY-2-PROPANOL), 3, II

IMO:
UN 1987, ALCOHOL, N.O.S., (ISOPROPYL ALCOHOL AND 1-PROPOXY-2-PROPANOL), 3, II, LIMITED QUANTITY

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com



Safety Data Sheet

Copyright, 2015 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 33-5600-3 | Version Number: | 2.00 |
| Issue Date: | 05/08/15 | Supersedes Date: | 09/02/14 |

SECTION 1: Identification

1.1. Product identifier

G84, Glass Compound (27-93A): G8416

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Remove heavy grit scratches from glass quickly while leaving a polished surface

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | Meguiar's, Inc. |
| DIVISION: | Meguiar's |
| ADDRESS: | 17991 Mitchell South, Irvine, CA 92614, USA |
| Telephone: | 949-752-8000 (Fax: 949-752-5784) |

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Skin Corrosion/Irritation: Category 2.

Specific Target Organ Toxicity (central nervous system): Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves.
Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.
37% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|-----------------------|------------|------------------------|
| Petroleum Distillates | 64742-88-7 | 10 - 30 Trade Secret * |
| Petroleum Distillates | 64742-48-9 | 1 - 10 Trade Secret * |
| Petroleum Distillates | 64742-47-8 | 3 - 7 Trade Secret * |

Any remaining components do not contribute to the hazards of this material.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|------------|-------------------------|--|---|
| Kerosine (petroleum) | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., Skin Notation |
| Petroleum Distillates | 64742-47-8 | CMRG | TWA:165 ppm | |
| Naphtha | 64742-48-9 | OSHA | TWA:400 mg/m3(100 ppm) | |
| Petroleum Distillates | 64742-48-9 | Manufacturer determined | TWA:100 ppm | |
| Kerosine (petroleum) | 64742-88-7 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., Skin Notation |
| Petroleum Distillates | 64742-88-7 | CMRG | TWA:100 ppm | |

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer
Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|--|
| General Physical Form: | Liquid |
| Odor, Color, Grade: | Creamy white liquid with sweet hydrocarbon odor |
| Odor threshold | <i>No Data Available</i> |
| pH | 8.6 - 9.1 |
| Melting point | <i>No Data Available</i> |
| Boiling Point | <i>No Data Available</i> |
| Flash Point | Flash point > 93 °C (200 °F) |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | <i>No Data Available</i> |
| Flammable Limits(UEL) | <i>No Data Available</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 1.1 - 1.2 g/ml |
| Specific Gravity | 1.1 - 1.2 [<i>Ref Std: WATER=1</i>] |
| Solubility in Water | <i>No Data Available</i> |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 22,000 - 36,000 centipoise |
| Hazardous Air Pollutants | <=0.00025 lb HAPS/lb solids [<i>Test Method: Calculated</i>] |

| | |
|---|--|
| Volatile Organic Compounds | 16.0 % weight [<i>Test Method:</i> calculated per CARB title 2] |
| Volatile Organic Compounds | 295 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| Percent volatile | 71.6 % weight |
| VOC Less H2O & Exempt Solvents | 656 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-----------------------|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE > 5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE > 50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| Petroleum Distillates | Inhalation-Vapor | | LC50 estimated to be 20 - 50 mg/l |
| Petroleum Distillates | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Petroleum Distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Petroleum Distillates | Inhalation-Vapor | | LC50 estimated to be 20 - 50 mg/l |
| Petroleum Distillates | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Petroleum Distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Petroleum Distillates | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| Petroleum Distillates | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 3.0 mg/l |
| Petroleum Distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|-----------------------|---------|---------------|
| Petroleum Distillates | Rabbit | Irritant |
| Petroleum Distillates | Rabbit | Irritant |
| Petroleum Distillates | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|-----------------------|---------|---------------------------|
| Petroleum Distillates | Rabbit | No significant irritation |
| Petroleum Distillates | Rabbit | No significant irritation |
| Petroleum Distillates | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|-----------------------|------------|-----------------|
| Petroleum Distillates | Guinea pig | Not sensitizing |
| Petroleum Distillates | Guinea pig | Not sensitizing |
| Petroleum Distillates | Guinea pig | Not sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|-----------------------|----------|--|
| Petroleum Distillates | In vivo | Not mutagenic |
| Petroleum Distillates | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | In vivo | Not mutagenic |
| Petroleum Distillates | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------|------------------|--|
| Petroleum Distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | Inhalation | Human and animal | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | Inhalation | Human and animal | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|--------------------------|---------|----------------|----------------------|
| Petroleum Distillates | Inhalation | Not toxic to development | Rat | NOAEL 2.4 mg/l | during organogenesis |
| Petroleum Distillates | Inhalation | Not toxic to development | Rat | NOAEL 2.4 mg/l | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|-----------------------------------|--|------------------|---------------------|-------------------|
| Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Petroleum Distillates | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 6.5 mg/l | 4 hours |
| Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Petroleum Distillates | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 6.5 mg/l | 4 hours |
| Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|---|--|-------------------------|----------------|-------------------|
| Petroleum Distillates | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 4.6 mg/l | 6 months |
| Petroleum Distillates | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 1.9 mg/l | 13 weeks |
| Petroleum Distillates | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL 0.6 mg/l | 90 days |
| Petroleum Distillates | Inhalation | bone, teeth, nails, and/or hair blood liver muscles | All data are negative | Rat | NOAEL 5.6 mg/l | 12 weeks |
| Petroleum Distillates | Inhalation | heart | All data are negative | Multiple animal species | NOAEL 1.3 mg/l | 90 days |
| Petroleum Distillates | Inhalation | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 4.6 mg/l | 6 months |
| Petroleum Distillates | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 1.9 mg/l | 13 weeks |
| Petroleum Distillates | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL 0.6 mg/l | 90 days |
| Petroleum Distillates | Inhalation | bone, teeth, nails, and/or hair blood liver muscles | All data are negative | Rat | NOAEL 5.6 mg/l | 12 weeks |
| Petroleum Distillates | Inhalation | heart | All data are negative | Multiple animal species | NOAEL 1.3 mg/l | 90 days |

Aspiration Hazard

| Name | Value |
|-----------------------|-------------------|
| Petroleum Distillates | Aspiration hazard |
| Petroleum Distillates | Aspiration hazard |
| Petroleum Distillates | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com



Safety Data Sheet

Copyright, 2014 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 33-5752-2 | Version Number: | 1.02 |
| Issue Date: | 05/23/14 | Supersedes Date: | 05/23/14 |

SECTION 1: Identification

1.1. Product identifier

G85, Glass Treatment (22-131C): G8508

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Water repellent glass coating

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | Meguiar's, Inc. |
| DIVISION: | Meguiar's |
| ADDRESS: | 17991 Mitchell South, Irvine, CA 92614, USA |
| Telephone: | 949-752-8000 (Fax: 949-752-5784) |

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Corrosive to metal: Category 1.
Flammable Liquid: Category 2.
Serious Eye Damage/Irritation: Category 2A.
Aspiration Hazard: Category 1.
Specific Target Organ Toxicity (central nervous system): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

May be corrosive to metals.

Highly flammable liquid and vapor.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Keep only in original container.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|------------------------|------------|--------------------------|
| Isopropyl Alcohol | 67-63-0 | 40 - 70 Trade Secret * |
| Petroleum Distillates | 64742-47-8 | 10 - 30 Trade Secret * |
| Poly(Dimethylsiloxane) | 63148-62-9 | 5 - 15 Trade Secret * |
| 1-Propoxy-2-Propanol | 1569-01-3 | 7 - 13 Trade Secret * |
| Sulfuric Acid | 7664-93-9 | 0.5 - 1.5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Aldehydes
 Formaldehyde
 Carbon monoxide
 Carbon dioxide
 Oxides of Sulfur

Condition

During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Occupational exposure limits

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--|------------|--------|--|---------------------|
| Kerosine (petroleum) | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³ | Skin Notation |
| Petroleum Distillates | 64742-47-8 | CMRG | TWA:165 ppm | |
| Isopropyl Alcohol | 67-63-0 | ACGIH | TWA:200 ppm;STEL:400 ppm | |
| Isopropyl Alcohol | 67-63-0 | OSHA | TWA:980 mg/m ³ (400 ppm) | |
| STRONG INORGANIC ACID MISTS CONTAINING SULFURIC ACID | 7664-93-9 | ACGIH | Limit value not established: | |
| Sulfuric Acid | 7664-93-9 | ACGIH | TWA(thoracic fraction):0.2 mg/m ³ | |
| Sulfuric Acid | 7664-93-9 | CMRG | TWA:1 mg/m ³ ;STEL:2 mg/m ³ | |
| Sulfuric Acid | 7664-93-9 | OSHA | TWA:1 mg/m ³ | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene
Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| General Physical Form: | Liquid |
| Odor, Color, Grade: | translucent liquid with characteristic chemical odor |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>No Data Available</i> |
| Boiling Point | 80 - 90 °C |
| Flash Point | 55 °F [<i>Test Method:</i> Closed Cup] |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | <i>No Data Available</i> |
| Flammable Limits(UEL) | <i>No Data Available</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 6.8429 lb/gal |
| Specific Gravity | 0.82 [<i>Ref Std:</i> WATER=1] |
| Solubility In Water | <i>No Data Available</i> |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 10 centipoise |
| Hazardous Air Pollutants | 0.00063096 lb HAPS/lb solids |
| Hazardous Air Pollutants | 0.00031548 % weight |
| Hazardous Air Pollutants | 0.000021588 lb HAPS/gal |
| Volatile Organic Compounds | 72.3 % [<i>Test Method:</i> calculated per CARB title 2] |
| Volatile Organic Compounds | 716 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| Volatile Organic Compounds | 5.98 lb/gal [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| Percent volatile | 87.4 % [<i>Test Method:</i> Estimated] |
| VOC Less H2O & Exempt Solvents | 716 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| VOC Less H2O & Exempt Solvents | 5.98 lb/gal [<i>Test Method:</i> calculated SCAQMD rule 443.1] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

Strong acids

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Class Description</u> | <u>Regulation</u> |
|--------------------------|--------------------------|---------------------------------|---|
| SULF ACID MISTS | 7664-93-9 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| SULF ACID MISTS | 7664-93-9 | Known human carcinogen | National Toxicology Program Carcinogens |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|------------------------|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE > 5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| Isopropyl Alcohol | Dermal | Rabbit | LD50 12,870 mg/kg |
| Isopropyl Alcohol | Inhalation-Vapor (4 hours) | Rat | LC50 72.6 mg/l |
| Isopropyl Alcohol | Ingestion | Rat | LD50 4,710 mg/kg |
| Petroleum Distillates | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| Petroleum Distillates | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 3.0 mg/l |
| Petroleum Distillates | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Poly(Dimethylsiloxane) | Dermal | Rabbit | LD50 > 19,400 mg/kg |
| Poly(Dimethylsiloxane) | Ingestion | Rat | LD50 > 17,000 mg/kg |
| 1-Propoxy-2-Propanol | Dermal | Rabbit | LD50 2,805 mg/kg |
| 1-Propoxy-2-Propanol | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 11.8 mg/l |
| 1-Propoxy-2-Propanol | Ingestion | Rat | LD50 2,500 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------------|-------------------------|---------------------------|
| Isopropyl Alcohol | Multiple animal species | No significant irritation |
| Petroleum Distillates | Rabbit | Mild irritant |
| Poly(Dimethylsiloxane) | Rabbit | No significant irritation |
| 1-Propoxy-2-Propanol | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------------------------|---------|---------------------------|
| Isopropyl Alcohol | Rabbit | Severe irritant |
| Petroleum Distillates | Rabbit | Mild irritant |
| Poly(Dimethylsiloxane) | Rabbit | No significant irritation |
| 1-Propoxy-2-Propanol | Rabbit | Severe irritant |

Skin Sensitization

| Name | Species | Value |
|-----------------------|------------|-----------------|
| Isopropyl Alcohol | Guinea pig | Not sensitizing |
| Petroleum Distillates | Guinea pig | Not sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|------|---------|-------|
| | | |

Germ Cell Mutagenicity

| Name | Route | Value |
|-----------------------|----------|---------------|
| Isopropyl Alcohol | In Vitro | Not mutagenic |
| Isopropyl Alcohol | In vivo | Not mutagenic |
| Petroleum Distillates | In Vitro | Not mutagenic |
| 1-Propoxy-2-Propanol | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------|---------|--|
| Isopropyl Alcohol | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| Petroleum Distillates | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|----------------------|------------|--|---------|---------------------|----------------------|
| Isopropyl Alcohol | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 400 mg/kg/day | during organogenesis |
| Isopropyl Alcohol | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | LOAEL 9 mg/l | during gestation |
| 1-Propoxy-2-Propanol | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 3.6 mg/l | during organogenesis |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------------|------------|-----------------------------------|--|-------------------------|---------------------|------------------------|
| Isopropyl Alcohol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Isopropyl Alcohol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Isopropyl Alcohol | Inhalation | auditory system | Some positive data exist, but the data are not sufficient for classification | Guinea pig | NOAEL 13.4 mg/l | 24 hours |
| Isopropyl Alcohol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness | | NOAEL Not available | |
| Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| 1-Propoxy-2-Propanol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | LOAEL 10.8 mg/l | 6 hours |
| 1-Propoxy-2-Propanol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| 1-Propoxy-2-Propanol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Rat | LOAEL 1,770 mg/kg | not applicable |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------------------|------------|-------------------------------|--|---------|---------------------|-------------------|
| Isopropyl Alcohol | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 12.3 mg/l | 24 months |
| Isopropyl Alcohol | Inhalation | nervous system | All data are negative | Rat | NOAEL 12 mg/l | 13 weeks |
| Isopropyl Alcohol | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 400 mg/kg/day | 12 weeks |
| 1-Propoxy-2-Propanol | Inhalation | liver kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 9.5 mg/l | 11 days |

Aspiration Hazard

| Name | Value |
|-----------------------|-------------------|
| Petroleum Distillates | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information**DOTG:**

LIMITED QUANTITY

DOTW:

UN 1987, ALCOHOL, N.O.S., (ISOPROPYL ALCOHOL AND 1-PROPOXY-2-PROPANOL), 3, II, LIMITED QUANTITY

IATA:

UN1987, ALCOHOL, N.O.S., (ISOPROPYL ALCOHOL AND 1-PROPOXY-2-PROPANOL), 3, II

IMO:

UN 1987, ALCOHOL, N.O.S., (ISOPROPYL ALCOHOL AND 1-PROPOXY-2-PROPANOL), 3, II, LIMITED QUANTITY

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact manufacturer for more information

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|-------------------|------------------|----------------|
| Sulfuric Acid | 7664-93-9 | 0.5 - 1.5 |

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 33-5752-2 | Version Number: | 1.02 |
| Issue Date: | 05/23/14 | Supersedes Date: | 05/23/14 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com