

# **Safety Data Sheet**

Copyright, 2014 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 33-8063-1 **Version Number:** 1.00

**Issue Date:** 08/08/14 **Supercedes Date:** Initial Issue

# **SECTION 1: Identification**

### 1.1. Product identifier

M197 Premium Polish and Sealant, (#26-23B): M19716

### 1.2. Recommended use and restrictions on use

### Recommended use

Paint protectant, Marine

1.3. Supplier's details

MANUFACTURER: Meguiar's, Inc. DIVISION: Meguiar's

ADDRESS: 17991 Mitchell South, Irvine, CA 92614, USA

**Telephone:** 949-752-8000 (Fax: 949-752-5784)

### 1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

# **SECTION 2: Hazard identification**

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## 2.2. Label elements

### Signal word

Not applicable.

## **Symbols**

Not applicable.

### **Pictograms**

Not applicable.

### 2.3. Hazards not otherwise classified

None.

25% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 80 Trade Secret *
Petroleum Distillates	64742-88-7	5 - 10 Trade Secret *
Petroleum Distillates	64742-47-8	5 - 10 Trade Secret *
Aluminum Oxide	1344-28-1	2 - 8 Trade Secret *
Petroleum Distillates	8042-47-5	1 - 5 Trade Secret *
Poly(Dimethylsiloxane)	63148-62-9	1 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact**

Wash with soap and water. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

## **5.3.** Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Aluminum Oxide	1344-28-1	CMRG	TWA:1 fiber/cc	
Aluminum Oxide	1344-28-1	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon	Skin Notation, A3:
			vapor, non-aerosol):200	Confirmed animal
			mg/m3	carcin.
Petroleum Distillates	64742-47-8	CMRG	TWA:165 ppm	
Petroleum Distillates	64742-88-7	CMRG	TWA:100 ppm	
MINERAL OILS,	8042-47-5	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
HIGHLY-REFINED OILS			mg/m3	carcin

\_\_\_\_\_

M197 Premium Polish and Sealant, (#26-23B): M19716 08/08/14

Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	
Petroleum Distillates	8042-47-5	CMRG	TWA:5 mg/m3;STEL:10	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## **8.2.2.** Personal protective equipment (PPE)

## Eye/face protection

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

Nitrile Rubber

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Sweet white
Odor threshold No Data Available

**pH** 8-9

Melting pointNo Data AvailableBoiling PointNo Data Available

Flash Point 200 °F

Evaporation rate

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

No Data Available
No Data Available
No Data Available
No Data Available

\_\_\_\_\_

Vapor Density No Data Available

Density1.18 g/mlSpecific Gravity1.18 g/cm3Solubility In WaterNo Data Available

**Solubility- non-water** No Data Available

Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data Available

Viscosity 20,000 - 28,000 centipoise

Volatile Organic Compounds 17.3 %

**Volatile Organic Compounds**205 g/l [Test Method: calculated SCAQMD rule 443.1] **Volatile Organic Compounds**1.72 lb/gal [Test Method: calculated SCAQMD rule 443.1]

VOC Less H2O & Exempt Solvents 1,104 g/l

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

## 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

## Based on test data and/or information on the components, this material may produce the following health effects:

### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-		No data available; calculated ATE > 50 mg/l
	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Petroleum Distillates	Inhalation-	Rat	LC50 > 3.0 mg/l
	Dust/Mist		
	(4 hours)		
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Petroleum Distillates	Inhalation-		LC50 estimated to be 20 - 50 mg/l
	Vapor		
Petroleum Distillates	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-	Rat	LC50 > 2.3  mg/l
	Dust/Mist		
	(4 hours)		
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Petroleum Distillates	Dermal	Rabbit	LD50 > 2,000 mg/kg
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

### **Skin Corrosion/Irritation**

Name	Species	Value
Petroleum Distillates	Rabbit	Mild irritant
Petroleum Distillates	Rabbit	Irritant
Aluminum Oxide	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Petroleum Distillates	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Serious Eje Bumuge/Himuton		
Name	Species	Value
Petroleum Distillates	Rabbit	Mild irritant
Petroleum Distillates	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Petroleum Distillates	Rabbit	Mild irritant

## **Skin Sensitization**

Name	Species	Value
Petroleum Distillates	Guinea	Not sensitizing
	pig	
Petroleum Distillates	Guinea	Not sensitizing
	pig	
Petroleum Distillates	Guinea	Not sensitizing
	pig	

**Respiratory Sensitization** 

Name	Species	Value

**Germ Cell Mutagenicity** 

Name	Route	Value
Petroleum Distillates	In Vitro	Not mutagenic
Petroleum Distillates	In vivo	Not mutagenic
Petroleum Distillates	In Vitro	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	In Vitro	Not mutagenic
Petroleum Distillates	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillates	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
Petroleum Distillates	Dermal	Mouse	Not carcinogenic
Petroleum Distillates	Inhalation	Multiple animal species	Not carcinogenic

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesi s
Petroleum Distillates	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Petroleum Distillates	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Petroleum Distillates	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

pecine rurger organ rowerty single exposure							
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration	
Petroleum Distillates	Inhalation	central nervous	May cause drowsiness or		NOAEL Not		
	1	system depression	dizziness		available		

Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
			data are not sufficient for		available	
			classification			
Petroleum Distillates	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
		system depression	dizziness	and	available	
				animal		
Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
			data are not sufficient for		available	
			classification			
Petroleum Distillates	Inhalation	nervous system	Some positive data exist, but the	Dog	NOAEL 6.5	4 hours
		-	data are not sufficient for	_	mg/l	
			classification		-	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Petroleum Distillates	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum Distillates	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Petroleum Distillates	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Petroleum Distillates	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Aluminum Oxide	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Petroleum Distillates	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,381 mg/kg/day	90 days
Petroleum Distillates	Ingestion	liver   immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,336 mg/kg/day	90 days

**Aspiration Hazard** 

Name	Value
Petroleum Distillates	Aspiration hazard
Petroleum Distillates	Aspiration hazard
Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

General Transportation Statement This product does not require classification by DOT, IATA, ICAO or IMDG.

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact manufacturer for more information

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## 15.2. State Regulations

Contact manufacturer for more information

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

## 15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

## NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

\_\_\_\_\_

M197 Premium Polish and Sealant, (#26-23B): M19716 08/08/14

Document Group:33-8063-1Version Number:1.00Issue Date:08/08/14Supercedes Date:Initial Issue

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com